# Q0112L125G

# LOAD CENTER QO MLO 240V 125A 1PH 12SP



#### Main

Product or component type	Load Center
Range of product	QO
Load center type	Main lugs
Line Rated Current	125 A
Number of spaces	12
Short-circuit current	65 kA
Number of circuits	12
Number of tandem circuit breakers	0
Phase	1 phase
System Voltage	120/240 V AC

### Complementary

AWG gauge	AWG 6AWG 2/0 (aluminium/copper)	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Order separately	
Electrical connection	Lugs	_
Device composition	Grounding bar included (not installed)	_
Electrical connection	Lugs	
Wiring configuration	3-wire	
Material	Tin plated copper busbar	
Enclosure material	Welded sheet steel	
Surface finish	Baked enamel grey	
Box number	6	_
Product certifications	UL listed	_
Height	17.91 in (455 mm)	
Width	14.25 in (362 mm)	

#### **Environment**

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1248 - Schneider Electric declaration of conformity	Compliant - since 1248 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

	·
Warranty period	10 months
warranty period	18 MONUS