



Principal

Producto	Interruptor automático en miniatura
Gama	QO
Current Rating ((*))	40 A
Voltage Rating ((*))	120 V AC 120/240 V AC 48 V DC
Tipo de montaje	Conexión
Número de polos	1P
Tipo de interruptor	Standard
Ratings ((*))	HACR rated ((*))
Electrical Connection ((*))	Box lugs ((*))

Complementario

Poder de corte	5 kA at: 48 V DC 10 kA at: 120/240 V AC 50/60 Hz 10 kA at: 120 V AC 50/60 Hz
Número de espacios necesarios	1
Wire Size ((*))	AWG 8...AWG 2 (copper or aluminium)
Altura	3.12 in
Profundidad	2.91 in
Anchura	0.75 in

Entorno

Certifications ((*))	CSA Registrado por UL
Temperatura ambiente de funcionamiento	40 °C

Sostenibilidad de la oferta

Estado de la oferta sostenible	Green Premium product
--------------------------------	-----------------------

RoHS (código de fecha: AASS)	Compliant - desde 1323 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Perfil ambiental del producto	Available
Instrucciones para el fin del ciclo de vida del producto	Need no specific recycling operations

Garantía contractual

Warranty period	18 months
-----------------	-----------